

G®-CUP E 272 – perfection down to the very last detail



- 8 Hinged doors**
- High rigidity due to the profiles
 - Can be rotated through 270 degrees
 - 3 mm thickness

- 2 Seals on the door frame and door**
- New integrated EPDM seal (tongue and groove system - also ideal for automatic washing facilities)

- 3 Bumpers**
- Replaceable, elastic blue PVC bumper on the top and base of the trolley
 - Top edging to secure the storage of small parts

- 4 Document frames**
- DIN A4 size inside on the right door
 - DIN A7 size outside on the right short side

- 5 Twist lock**
- Easy to use, centrally operated
 - Contact pressure against the door frame seal
 - Easy and secure locking, even in the case of overfilling
 - Doors do not spring open during transport by truck

- 6 Shelf supports**
- Made of polyamide

- 7 Door hinges**
- Continuously from top to bottom
 - Maintenance-free and silent due to the Teflon-coated hinge pins

- 9 Trolley undercarriage**
- Optimum torsional stiffness
 - High degree of stability due to the BiTubAl® frame (two tubular system profiles connected to the trolley undercarriage)
 - Adjustable wheel positions
 - Smooth running, even when trolleys are towed in train

- 10 Handles**
- Ergonomic handles in 2 versions
 - Combined push/pull handle on both short sides
 - Easy push handle
 - Pull handle ensures maximum safety at work

- 11 Magnets**
- For securing the open doors on both short sides

- 12 Undercarriage**
- 2 swivel castors with brakes and 2 fixed castors
 - Supratech wheels, 200 mm diameter wheel, precision ball bearings, thermoplastic rubber tread, non-marking
 - Many optional alternatives (e.g. for use in sterile areas)
 - Adaptable for AGV
 - Wheel positions can be adjusted