G®-ERGO flex



Aluminum order picking cart





Click here for the G®-ERGO flex video



We bring flexibility to your logistics!

G®-ERGO flex

With continuous adjustable spring force: The optimal solution for your logistics!

ADVANTAGES:

- Individually adjustable spring force depending on the product - fastest work at the highest level!
- Intuitive operation without prior knowledge
- Constant loading and unloading height even with goods of different weights
- Unique on the market
- Made of anodised aluminum light, robust and abrasion resistant

SIMPLE OPERATION:

- Spring force easily adjustable lightly pull the handle upwards and then slide it
- Continuously adjustable in the working process
- Spring force from approx. 25 to 70 kg - continuous adjustment range of approx. 45 kg
- Flexible adjustment possible at any time



Technical data

Model number	Wheel arrangement	DimensionsLxW internal	/xH(approx.mm) external	Volume (approx.l)		Spring force (approx. kg)			Order no.
D 5405 ERGO flex	E	1070 x 740 x 610	1180 x 780 x 895	480	125	25 - 70	130	56	022540501
D 5405 ERGO flex quick grip	E	1070 x 740 x 610	1435 x 780 x 1 040	480	125	25 - 70	130	58	222540502

- All-round PVC bumper on the upper edge of the trolley
- With closed base for driving underneath with pallet truck or fork-lift truck
- Wheel arrangement E: 4 swivel castors, 2 with wheel brakes and one fixed castor, with spring suspension for secure floor contact and good directional stability
- Manufactured according to European standard EN 1757
- Option: ergonomic push handle





Narrower gap with plastic rim inlay or brush strip



Ladder, push aid, drink holder, scanner holder, label dispenser, writing tablet or clipboard



Wheel arrangement E: 4 swivel castors, 2 with wheel brakes and 1 fixed castor

Special solutions

Available on request! We respond to your individual wishes and needs, for different dimensions, spring forces, different handles, ladder, bumpers and wheels contact us.

Individual solutions are our business - We will find YOUR solution!